



## safe-T-seat Assembly Instructions

### Parts List

Stinger

Bracket

Hex Key

Cap Screws (2)

Ring Pin

Clip



**IMPORTANT:** This bicycle carrier must be installed in strict accordance with the instructions provided. The instructions should be read carefully and each step followed carefully and completely.


1. Looking at the bottom of the seat, remove the assembled stinger and bracket from the seat plate by removing the ring pin and clip. Then remove 1 cap screw from the bracket.




2. Place the partially assembled pieces around the handlebar stem and insert the other screw. Again, make sure the arrow and the hollow part of the stinger are facing up. (It may be necessary to raise the handle bar stem to accommodate the stinger assembly.)



3. Tighten both screws the same length with the hex key so there is even pressure on the bracket. Before tightening the screws completely, make sure the stinger is aligned with the tire & frame. **Do Not over tighten.**



4. Slide seat onto stinger as far forward as possible. Secure the stinger to the seat plate by sliding the ring pin through the holes. Fasten the ring pin with the clip. Never place a child in the seat until ALL parts are secured properly. The seat will not slide along the stinger when the seat is fastened correctly.



5. Holding onto the bike, put child in the seat and pull straps over the child's head. Adjust length so straps are snug on child's shoulders. Slide the stabilizer on the straps up to the child's chest (approx. 3 inches below the chin). Clip the shoulder straps into the crotch strap.

6. Enjoy your ride!!!

Failure to comply with these manufacturer's instructions can lead to serious injury of the passenger/rider!